



SUNLINK ENERGY
Better Energy Better Life

Sunlink Energy Limited

NEW! 20W SEMI-Flexible Mono Solar Panel+ 5A solar regulator + 5m cable, battery clips perfect kit for motorhome,caravan,camper,boat...

The flexible solar panel is light, durable and small.

It can be bonded directly to a roof.

Its warterproof, perfect to use on yacht, car, boat, snow mobile, golf-cart. Can sit, stamp on it.

We can produce the panel's dimension by customer's request.

Packing:

1 x 20w Mono Semi-flexible solar panel

1 x 5A solar regulator

1 x 5m cable, battery clips



Highly efficient monocrystalline cells
Laminated for weather resistance
laminated with oxide aluminum + EVA + Silicon cell + EVA + Tedlar
Size: 730,300,2.5mm peak(Wp): 20w
Open circuit voltage(Voc): 21V
Optimum power voltage(VMP): 18V
Short circuit current(Isc): 1.24
Max operating current(IMP): 1.12
torrence: +_5% weight: 1.5kgs



SUNLINK ENERGY
Better Energy Better Life

Sunlink Energy Limited

NEW! 30W semi-flexible Mono Solar Panel+ 5A solar regulator+5M cable

The flexible solar panel is light, durable and small.

It can be bonded directly to a roof.

Its warterproof, perfect to use on yacht, car, boat, snow mobile, golf-cart. Can sit, stamp on it.

We can produce the panel's dimension by customer's request.

Packing:

1 x 30w Mono Semi-flexible solar panel

1 x 5A solar regulator

1 x 5m cable, battery clips



Highly efficient monocrystalline cells
Laminated for weather resistance
laminated with oxide aluminum + EVA + Silicon cell + EVA + Tedlar
Size: 640,440,2.5mm peak(Wp): 30w
Open circuit voltage(Voc): 21V
Optimum power voltage(VMP): 18V
Short circuit current(Isc): 1.89
Max operating current(IMP): 1.72
torrence: +_5% weight: 1.5kgs



SUNLINK ENERGY
Better Energy Better Life

Sunlink Energy Limited

New!40W semi-flexible Mono Solar Panel+
5A solar regulator
+ 5m cable, battery clips

The flexible solar panel is light, durable and small.

It can be bonded directly to a roof.

Its warterproof, perfect to use on yacht, car, boat,
snow mobile, golf-cart. Can sit, stamp on it.

We can produce the panel's dimension by
customer's request.

Packing:

- 1 x 40w Mono Semi-flexible solar panel**
- 1 x 5A solar regulator**
- 1 x 5m cable, battery clips**

40W Flexible Solar Panels Kit



Highly efficient monocrystalline cells
Laminated for weather resistance
laminated with oxide aluminum + EVA + Silicon cell + EVA + Tedlar
Size: 760,440,2.5mm peak(Wp): 40w
Open circuit voltage(Voc): 21V
Optimum power voltage(VMP): 18V
Short circuit current(Isc): 2.25
Max operating current(IMP): 2.22
torrence: +_5% weight: 2kgs



SUNLINK ENERGY
Better Energy Better Life

Sunlink Energy Limited

50W semi-flexible Mono Solar Panel+ 5 A solar regulator,5m cable with battery clips

The flexible solar panel is light, durable and small. It can be bonded directly to a roof.

Its warterproof, perfect to use on yacht, car, boat, snow mobile, golf-cart. Can sit, stamp on it.

We can produce the panel's dimension by customer's request.

Packing:

1 x 50w Mono Semi-flexible solar panel

1 x 5A solar regulator

1 x 5m cable, battery clips

50W Flexible Solar Panels Kit



Highly efficient monocrystalline cells
Laminated for weather resistance
laminated with oxide aluminum + EVA + Silicon cell + EVA + Tedlar
Size: 880,440,2.5mm peak(Wp): 50w
Open circuit voltage(Voc): 21V
Optimum power voltage(VMP): 18V
Short circuit current(Isc): 3.1
Max operating current(IMP): 2.8
torrence: +_5% weight: 2.5kgs



SUNLINK ENERGY
Better Energy Better Life

Sunlink Energy Limited

NEW! 60W semi-flexible Mono Solar Panel+ 5 A solar regulator,5m cable with battery clips The flexible solar panel is light, durable and small. It can be bonded directly to a roof.
It's waterproof, perfect to use on yacht, car, boat, snow mobile, golf-cart. Can sit, stamp on it. We can produce the panel's dimension by customer's request.

Packing:

- 1 x 60w Mono Semi-flexible solar panel**
- 1 x 5A solar regulator**
- 1 x 5m cable, battery clips**

60W Flexible Solar Panels Kit



Highly efficient monocrystalline cells
Laminated for weather resistance
laminated with oxide aluminum + EVA + Silicon cell + EVA + Tedlar
Size: 900,570,2.5mm peak(Wp): 60w
Open circuit voltage(Voc): 21V
Optimum power voltage(VMP): 18V
Short circuit current(Isc): 3.67
Max operating current(IMP): 3.34
tolerance: +_5% weight: 3kgs



SUNLINK ENERGY
Better Energy Better Life

Sunlink Energy Limited

80W semi-flexible Mono Solar Panel + 10 A solar regulator, 5m cable with battery clips

The flexible solar panel is light, durable and small. It can be bonded directly to a roof.

It's waterproof, perfect to use on yacht, car, boat, snow mobile, golf-cart. Can sit, stamp on it. We can produce the panel's dimension by customer's request.

Packing:

1 x 80w Mono Semi-flexible solar panel

1 x 5A solar regulator

1 x 5m cable, battery clips



Highly efficient monocrystalline cells
Laminated for weather resistance
laminated with oxide aluminum + EVA + Silicon cell + EVA + Tedlar
Size: 1100,570,2.5mm peak(Wp): 80w
Open circuit voltage(Voc): 21V
Optimum power voltage(VMP): 18V
Short circuit current(Isc): 4.95
Max operating current(IMP): 4.45
tolerance: +_5% weight: 4kgs



5m cable with battery clips



12V 5A/10A solar panel regulator charge controller



Function: Battery Overcharge and charge protection; Battery Open-circuited protection; Load Over-voltage protection; Reversed charge protection at night; Flow and short circuit protection; Battery Open-circuited protection; Solar Cells Reversed protection; Over-voltage protection; Temperature Compensation (automatic identification of the temperature sensor is online)

Model	Over discharge parameter		Over voltage parameter		Charge parameter		Working method	Status indication	No-load current (A)	Fault alarm
	Over discharge protection	Over discharge resume	Over voltage protection	Over voltage resume	Average protection	Average resume				
JC12 5A	11.1V±1%	13.2V±1%	16.5V±1%	15.0V±1%	14.4V±1%	13.3V±1%	Manual switch	LED	≤0.01	Custom made
JC12 10A	11.1V±1%	13.2V±1%	16.5V±1%	15.0V±1%	14.4V±1%	13.3V±1%	Manual switch	LED	≤0.01	Custom made